

Features 特色

1. The thickness of the specially made fireproof door canvas, can be selected from 0.8mm to 2.0mm thick materials for different usage's and has 10 optional colours.
 2. Every "Instant Roll" door is equipped with a manual operation handle, to open and close the door easily even during power failures.
 3. Double photoelectric cells prevent the door from falling closed while in use.
 4. Transparent windows in the door improve working safety and working efficiency.
1. 特殊材質的防火布簾可依照用途選擇0.8到2.0mm的厚度範圍，且有十種顏色以供選擇。
 2. 每扇快速捲門皆配備有手動搖桿，可輕易開啓或關閉，以避免於停電或故障情形發生時，造成工作停頓或產生危險。
 3. 靈敏的雙光電感應裝置可防止布簾於人員、車輛通過時降下。
 4. 布簾的透明視窗增進工作的安全性及管理的便易性。

Data 資料	Model 型號	IR-N	IR-L
Application 適用地點		Indoor/Outdoor 室內、室外	Cold Storage 冷藏庫
Max. Dimension 最大尺寸		4m(W)×4m(H)	4m(W)×4m(H)
Max. O / C Speed 開關速度		250 cm / sec	120 cm / sec
Bearable Speed 可抗風速		100 Km / hr	60 Km / hr
Canvas Thickness 布簾厚度		0.8 ~ 2.0 mm	2.0 mm

Remarks :

1. Customer's trade mark can be printed on the door canvas.
2. Power supply is 3 ϕ × 220 / 380 / 440V
3. Sensing Methods include :
Radar, electro magnetic field, photo-electric cell, remote control, manual, and PLC connection.

附註 :

1. 在布簾表面可印刷顧客公司的商標。
2. 電源供應為3相、220、380或440伏特。
3. 感應方式有以下等方式：
雷達、線圈感應、光電感應、遙控器、手動搖桿或PLC連線。



Two "Instant Roll" doors mounted 10cm apart, can provide significantly improved soundproofing and thermal insulation.

保溫型快速捲門具有兩層布簾，布簾之間相距10公分，所以擁有絕佳的保溫、隔音效果。